



### Main

Range of product	Modicon M221
Product or component type	Serial line cartridge
Product compatibility	Modicon M221C

### Complementary

Integrated connection type	Non isolated serial link - screw terminal block for RS232 Non isolated serial link - screw terminal block for RS485
Transmission rate	1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 15 m for RS485 1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 3 m for RS232
Communication port protocol	Non isolated serial link: Modbus master/slave - RTU/ASCII or SoMachine-Network
Insulation	Non-insulated between lines and internal logic
Height	41 Mm
Depth	15 Mm
Width	35 Mm
Net weight	0.015 Kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

Product Life Status : **Commercialised**