



### Main

Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Motor control Resistive load
Utilisation category	AC-4 AC-1 AC-3
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	1000 A (at <40 °C) at <= 440 V AC AC-1 800 A (at <55 °C) at <= 440 V AC AC-3
Motor power kW	450 KW at 1000 V AC 50/60 Hz (AC-3) 450 KW at 500 V AC 50/60 Hz (AC-3) 475 KW at 660...690 V AC 50/60 Hz (AC-3) 110 KW at 400 V AC 50/60 Hz (AC-4) 450 KW at 380...400 V AC 50/60 Hz (AC-3) 450 KW at 415 V AC 50/60 Hz (AC-3) 450 KW at 440 V AC 50/60 Hz (AC-3) 250 KW at 220...230 V AC 50/60 Hz (AC-3)
[Uc] control circuit voltage	220...230 V DC 220...240 V AC 40...400 Hz
Coil type	Standard

### Complementary

[Uimp] rated impulse withstand voltage	8 KV
Overvoltage category	III
[Ith] conventional free air thermal current	1000 A (at 40 °C)
Rated breaking capacity	6400 A conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	5500 A 40 °C - 10 s 4600 A 40 °C - 30 s 3600 A 40 °C - 1 min 2600 A 40 °C - 3 min 1700 A 40 °C - 10 min
Associated fuse rating	1000 A gG at <= 440 V 800 A aM at <= 440 V
Average impedance	0.12 MOhm - Ith 1000 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C
Power dissipation per pole	120 W AC-1 77 W AC-3

Mounting support	Plate
Standards	IEC 60947-1 JIS C8201-4-1 EN 60947-4-1 EN 60947-1 IEC 60947-4-1
Product certifications	ABS UL CCC CSA RMRoS CB
Connections - terminals	Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end Power circuit: bar 2 cable(s) - busbar cross section: 60 x 5 mm Power circuit: bolted connection
Tightening torque	Control circuit: 1.2 N.m Power circuit: 58 N.m
Control circuit voltage limits	Operational: 0.85...1.1 U <sub>c</sub> (at 55 °C) Drop-out: 0.3...0.5 U <sub>c</sub> (at 55 °C)
Inrush power in W	1900 W (at 20 °C)
Hold-in power consumption in W	12 W at 20 °C
Heat dissipation	12 W
Operating time	40...50 ms opening 60...80 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	600 Cyc/H 55 °C
Compatibility code	LC1F
Power range	250...500 KW at 200...240 V 3 phases 250...500 KW at 380...440 V 3 phases 110...220 KW at 200...240 V 3 phases 250...500 KW at 480...500 V 3 phases
Motor starter type	Direct on-line contactor
Contactor coil voltage	220 V DC standard 230 V DC standard 220 V AC standard 230 V AC standard 240 V AC standard

## Environment

IP degree of protection	IP20 front face with shrouds conforming to IEC 60529 IP20 front face with shrouds conforming to VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-5...55 °C
Height	304 Mm
Width	309 Mm
Depth	255 Mm
Net weight	18.75 Kg

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	18.455 Kg
Package 1 Height	33 Cm
Package 1 width	33.5 Cm

Package 1 Length	44 Cm
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Weight	82.32 Kg
Package 2 Height	80 Cm
Package 2 width	80 Cm
Package 2 Length	60 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------