



Main

| | |
|---------------------------|-------------------------------|
| Range of product | Masterpact NW |
| Product or component type | Basic frame |
| Device short name | Masterpact NW12 |
| Circuit breaker name | Masterpact NW12H1 |
| Poles description | 3P |
| Network type | AC |
| Breaking capacity code | H1 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category B |

Complementary

| | |
|---|--|
| Network frequency | 50/60 Hz |
| Control type | Push-button |
| Mounting mode | Drawout |
| [In] rated current | 1250 A at 40 °C |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 12 KV conforming to IEC 60947-2 |
| [Icm] rated short-circuit making capacity | 143 KA 525 V AC at 50/60 Hz 143 KA 690 V AC at 50/60 Hz |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Circuit breaker CT rating | 1250 A |
| Breaking capacity | 65 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 65 KA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2 65 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 65 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 65 KA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 65 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 65 KA at 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Protection type | Without protection |
| Mechanical durability | 12500 Cycles without maintenance conforming to IEC 60947-2 25000 Cycles with maintenance conforming to IEC 60947-2 |

| | |
|--|---|
| Electrical durability | 10000 Cycles 440 V AC 50/60 Hz without maintenance conforming- to IEC 60947-2 10000 Cycles 690 V AC 50/60 Hz without maintenance conforming- to IEC 60947-2 AC-23A: 10000 cycles 440 V AC 50/60 Hz without maintenance conforming- to IEC 60947-2 AC-23A: 10000 cycles 690 V AC 50/60 Hz without maintenance conforming- to IEC 60947-2 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming- to IEC 60947-2 |
| Connection pitch | 115 Mm |
| [Icw] rated short-time withstand current | 36 KA 3 s conforming to IEC 60947-2 65 KA 1 s conforming to IEC 60947-2 |
| Maximum breaking time | 25 Ms |
| Maximum closing response time | 70 Ms |
| Height | 439 Mm |
| Width | 441 Mm |
| Depth | 394.5 Mm |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | IEC 60947-2 |
| Product certifications | ASTA |
| Pollution degree | 4 conforming to IEC 60664-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**

48259 may be replaced by any of the following products:



LV848259

Circuit breaker Masterpact MTZ2 12H1, 1250 A, 3P drawout, without Micrologic

Qty 1

Reason for Substitution: End of life | Substitution date: 31 Dec 2019 |