



Commercial status

Discontinued on: 31 December 2018

To be end-of-service on: 31 December 2026

ⓘ Restricted Sales for Services

Main

Range of product	Modicon Premium Automation platform
Product or component type	Discrete output module
Discrete output number	32
Discrete output type	Solid state protected
Discrete output voltage	24 V DC positive conforming to EN/IEC 61131-2 19...30 V

Complementary

Current per channel	0.1 A
Maximum current per module	3.2 A
Maximum leakage current	0.1 mA, at 30 V
Maximum tungsten load	1.2 W
[Ures] residual voltage	1.5 V
Response time	1.2 ms
Paralleling of outputs	Yes : 3 maximum
Output overvoltage protection	By transil diode
Reverse polarity protection	Reverse mounted diode
Output overload protection	Automatic trip
Short-circuit protection	Automatic trip
Minimum load impedance	220 W at state 1
Isolation resistance	> 10 MOhm 500 V
Power dissipation	(1.6 W + 0.1 W x No of outputs)
Product compatibility	Dial and Power
Marking	CE
Electrical connection	2 connectors HE-10
Current consumption	140 mA at 5 V DC
Module format	Standard
Net weight	0.3 kg

Environment

Dielectric strength	1500 V 50/60 Hz 60 s
---------------------	----------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 142 CSA C22.2 No 213 Class I Division 2 Group D 73/23/EEC CSA C22.2 No 213 Class I Division 2 Group C IEC 61131-2 89/336/EEC UL 508 92/31/EEC 93/68/EEC
Product certifications	ABS RINA GL DNV RMRS LR BV
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	417 g
Package 1 Height	5.5 cm
Package 1 width	18 cm
Package 1 Length	26 cm

Contractual warranty

Warranty	18 months
----------	-----------

TSXDSY32T2K is replaced by:



Standard environment BMXDDO3202K

discrete output module X80 - 32 outputs - solid state - 24 V DC positive

Qty 1

Reason for Substitution: End of life | Substitution date: 30 September 2019 | This is not interchangeable but an equivalent functional product in the Modicon M580/X80 range. Please contact technical support about your migration options.