



### Commercial status

Discontinued on: 31 December 2018

To be end-of-service on: 31 December 2026

ⓘ Restricted Sales for Services

### Main

Range of product	Modicon Premium Automation platform
Product or component type	Non-extendable rack
Product specific application	For single rack configuration

### Complementary

Number of slots	12
Product compatibility	TSXPSY power supply TSXP57 processor Specific application module I/O module
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)
Marking	CE
Net weight	2.31 kg

### Environment

Standards	CSA C22.2 No 213 Class I Division 2 Group C 92/31/EEC CSA C22.2 No 213 Class I Division 2 Group A UL 508 73/23/EEC 93/68/EEC 89/336/EEC CSA C22.2 No 213 Class I Division 2 Group D IEC 61131-2 CSA C22.2 No 142 CSA C22.2 No 213 Class I Division 2 Group B
Product certifications	RINA ABS BV DNV GL LR RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.284 kg
Package 1 Height	5.5 cm
Package 1 width	12 cm
Package 1 Length	57 cm
Unit Type of Package 2	S04
Number of Units in Package 2	7
Package 2 Weight	16.93 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Contractual warranty

Warranty	18 months
----------	-----------

## TSXRKY12 is replaced by:



### Standard environment BMXXBP1200

rack M340 -12 slots - panel or plate mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 30 September 2019 | This is not interchangeable but an equivalent functional product in the Modicon M580/X80 range. Please contact technical support about your migration options.