Product data sheet Characteristics

TSXRKY6EX

extendable rack - for multi-racks configuration - 6 slots - IP20



Commercial status

Discontinued on: 31 December 2018

To be end-of-service on: 31 December 2026

Main

Range of product

Product or component type	Extendable rack	
Product specific application	For multi-racks configuration	
Complementary		
Number of slots	6	
Product compatibility	Specific application module	
	TSXPSY power supply	
	I/O madula	;

Modicon Premium Automation platform

1.5 kg

1 Toddet compatibility	TSXPSY power supply I/O module TSXP57 processor	
Electrical connection	2 connectors female SUB-D 9 (remote connection of bus X)	
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)	
Marking	CE	

Environment

Net weight

Standards	IEC 61131-2	— sn		
	CSA C22.2 No 213 Class I Division 2 Group A UL 508			
	CSA C22.2 No 213 Class I Division 2 Group D	and is		
	92/31/EEC	for		
	73/23/EEC	substitute for		
	CSA C22.2 No 213 Class I Division 2 Group B	ostit		
	CSA C22.2 No 213 Class I Division 2 Group C	sul		
	89/336/EEC	as as		
	CSA C22.2 No 142	ged 8		
Product certifications	ABS	not intended as		
	BV	i to		
	RINA			
	RMRS	tion		
	LR	ntai		
	DNV	Ę.		
	GL	documentation is		
Ambient air temperature for operation	060 °C	This		
		— ::		

Ambient air temperature for storage	ure for storage -2570 °C	
Relative humidity 1095 % without condensation for operation 595 % without condensation for storage		
Operating altitude	02000 m	
Protective treatment	TC	
IP degree of protection	IP20	
Pollution degree	2	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.306 kg
Package 1 Height	5.5 cm
Package 1 width	21 cm
Package 1 Length	34.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	9
Package 2 Weight	11.754 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Contractual warranty

Warranty	18 months	

TSXRKY6EX is replaced by:

Standard environment BMXXBP0800



Qty 1

rack M340 - 8 slots - panel, plate or DIN rail mounting

Reason for Substitution: End of life | Substitution date: 30 September 2019 | This is not interchangeable but an equivalent functional product in the Modicon M580/X80 range. Please contact technical support about your migration options.