
Product data sheet Characteristics

TSXRKY8

non-extendable rack - for single rack configuration - 8 slots - IP20



Commercial status

Discontinued on: 31 December 2018

To be end-of-service on: 31 December 2026

Main

Range of product

		•
Product or component type	Non-extendable rack	
Product specific application	For single rack configuration	
		<u> </u>
Complementary		
Number of slots	8	
Product compatibility	I/O module	

Modicon Premium Automation platform

1.75 kg

Product compatibility	I/O module TSXP57 processor Specific application module TSXPSY power supply
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)
Marking	CE

Environment

Net weight

Standards	73/23/EEC	substitute for and is not to be used for
	CSA C22.2 No 213 Class I Division 2 Group B	9
	93/68/EEC	7
	92/31/EEC	\$
	UL 508	2
	89/336/EEC	. <u>.</u> 7
	IEC 61131-2	ā
	CSA C22.2 No 213 Class I Division 2 Group D	. 2
	CSA C22.2 No 142	4
	CSA C22.2 No 213 Class I Division 2 Group A	2
	CSA C22.2 No 213 Class I Division 2 Group C	ď
Product certifications	BV	
	LR	5
	GL	
	DNV	2
	RINA	. <u>u</u> ?
	RMRS	
	ABS	6
Ambient air temperature for operation	060 °C	docimentation is not intended as
Ambient air temperature for storage	-2570 °C	i d
Relative humidity	1095 % without condensation for operation	
		7

5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.607 kg
Package 1 Height	5 cm
Package 1 width	21 cm
Package 1 Length	41.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	6
Package 2 Weight	9.642 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Contractual warranty

Warranty	18 months
----------	-----------

TSXRKY8 is replaced by:

Standard environment BMXXBP0800



rack M340 - 8 slots - panel, plate or DIN rail mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 30 September 2019 | This is not interchangeable but an equivalent functional product in the Modicon M580/X80 range. Please contact technical support about your migration options.