



### Commercial status

Discontinued on: 31 December 2019

To be end-of-service on: 31 December 2027

TSXDSZ32R5 has not been replaced. Please contact your customer care center for more information.

ⓘ Restricted Sales for Services

### Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Relay discrete output module
Discrete output number	32 screw terminal block
Contacts type and composition	NO

### Complementary

Output voltage limits	19...264 V AC 10...34 V DC
[Ith] conventional free air thermal current	2 A
Power consumption in VA	50 VA 24 V AC-12 resistive 24 VA 24 V AC-15 inductive 100 VA 48 V AC-12 resistive 200 VA 110...120 V AC-12 resistive 200 VA 200...240 V AC-12 resistive 50 VA 48 V AC-15 inductive 50 VA 110...120 V AC-15 inductive 50 VA 200...240 V AC-15 inductive
Power consumption in W	24 V DC-13 inductive 24 V DC-12 resistive
Response time	< 10 ms
Current consumption	175 mA
Power dissipation in W	3.5 W
Isolation voltage	1500 V for 1 s
Insulation resistance	>= 10 mOhm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	641 g
Package 1 Height	5.5 cm
Package 1 width	18 cm
Package 1 Length	26 cm

Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	5.5 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	<a href="#">China RoHS declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------

Pre-Actuators/Outputs Connections

Wiring Diagram

