# XALE1011

control station XAL-E - 1 flush pushbutton - spring return - green - 1 NO

Green Premium™



## Main

| | |
|---|---|
| Range of product | Harmony XALE |
| Product or component type | Complete control station |
| Device short name | XALE |
| Product destination | For XB7 Ø 22 mm control and signalling units |
| Control station application | One function |
| Colour of base of enclosure | Light grey (RAL 7035) |
| Colour of cover | Light grey (RAL 7035) |
| Material | ABS (acrylonitrile butadiene-styrene) |
| IP degree of protection | IP54 conforming to IEC 60529 |
| Control station composition | 1 flush push-button, green, spring return 1 NO |
| Contact operation | Slow-break |

## Complementary

| | |
|---|---|
| Cable entry | 2 knock-outs, clamping capacity: 16 mm<br> 4 knock-outs for ISO M20 |
| Net weight | 0.1 Kg |
| Marking | CE |
| Positive opening | Without |
| Short-circuit protection | 4 A cartridge fuse type gG conforming to EN/IEC 60947-5-1 |
| [Ui] rated insulation voltage | 250 V (pollution degree 3) conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 4 KV EN/IEC 60947-1 |
| [Ie] rated operational current | 0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.22 A at 125 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.3 A at 240 V, AC-14, D300 conforming to EN/IEC 60947-5-1<br>0.6 A at 120 V, AC-14, D300 conforming to EN/IEC 60947-5-1 |
| Electrical reliability | $\Lambda$ <= 10exp(-6) at 17 V and 5 mA conforming to IEC 60947-5-4 |

## Environment

| | |
|---|---|
| Protective treatment | TC |
| Ambient air temperature for storage | -40…70 °C |
| Ambient air temperature for operation | -25…55 °C |
| Electrical shock protection class | Class II conforming to IEC 60536 |
| IK degree of protection | IK05 conforming to EN 50102 |
| Standards | EN/IEC 60947-1<br>EN/IEC 62208<br>EN/IEC 60947-5-5<br>EN/IEC 60947-5-1 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 110 G |
| Package 1 Height | 10 Cm |
| Package 1 width | 11.4 Cm |
| Package 1 Length | 7.9 Cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 25 |
| Package 2 Weight | 3.241 Kg |
| Package 2 Height | 30 Cm |
| Package 2 width | 30 Cm |
| Package 2 Length | 40 Cm |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |

| Product Life Status : | Commercialised |
|---|---|