# Product data sheet
## Characteristics

# XALEK1701
control station XAL-E - emergency switching off function - 1 NC

Green Premium™ Product



## Main

| | |
|---|---|
| Range of product | Harmony XALE |
| Product or component type | Complete control station |
| Device short name | XALE |
| Product destination | For XB7 Ø 22 mm control and signalling units |
| Control station application | Emergency switching off function |
| Colour of base of enclosure | Light grey (RAL 7035) |
| Colour of cover | Yellow (RAL 1021) |
| Material | ABS (acrylonitrile butadiene-styrene) |
| IP degree of protection | IP54 conforming to IEC 60529 |
| Control station composition | 1 mushroom head push-button, red, latching 1 NC |
| Contact operation | Slow-break |

## Complementary

| | |
|---|---|
| Cable entry | 2 knock-outs, clamping capacity: 16 mm<br> 4 knock-outs for ISO M20 |
| Net weight | 0.11 Kg |
| Marking | CE |
| Positive opening | With conforming to EN/IEC 60947-5-1 appendix K |
| Short-circuit protection | 4 A cartridge fuse type gG conforming to EN/IEC 60947-5-1 |
| [Ui] rated insulation voltage | 250 V (pollution degree 3) conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | EN/IEC 60947-1 4 kV |
| [Ie] rated operational current | 0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br> 0.22 A at 125 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br> 0.3 A at 240 V, AC-14, D300 conforming to EN/IEC 60947-5-1<br> 0.6 A at 120 V, AC-14, D300 conforming to EN/IEC 60947-5-1 |
| Electrical reliability | $\Lambda <= 10exp(-6)$ at 17 V and 5 mA conforming to IEC 60947-5-4 |

## Environment

| | |
|---|---|
| Protective treatment | TC |
| Ambient air temperature for storage | -40…70 °C |
| Ambient air temperature for operation | -25…55 °C |
| Electrical shock protection class | Class II conforming to IEC 60536 |
| IK degree of protection | IK05 conforming to EN 50102 |
| Standards | EN/IEC 62208<br> EN/IEC 60947-5-1<br> EN/IEC 60947-1<br> EN/IEC 60947-5-5 |

Jul 31, 2021

Schneider Electric

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 128 G |
| Package 1 Height | 9.8 Cm |
| Package 1 width | 8.5 Cm |
| Package 1 Length | 11.6 Cm |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |

Product Life Status :     Commercialised