

Product datasheet

Specifications



C60 - circuit breaker - C60N - 3P - 50A - C curve

24355

- ❗ Discontinued on: 23 January 2021
- ❗ End-of-service on: 24 January 2021

❗ Discontinued

Main

Range of product	C60
Range	Multi 9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	50 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	6000 A Icn at 400 V AC conforming to IEC 60898 10 kA Icu at 400...415 V AC conforming to EN/IEC 60947-2 20 kA Icu at 230...240 V AC conforming to EN/IEC 60947-2 6 kA Icu at 440 V AC conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

[Ue] rated operational voltage	440 V AC 400 V AC 400...415 V AC 230...240 V AC
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	15 kA conforming to EN/IEC 60947-2 - 230...240 V AC 4.5 kA conforming to EN/IEC 60947-2 - 440 V AC 7.5 kA conforming to EN/IEC 60947-2 - 400...415 V AC 6000 A conforming to IEC 60898 - 400 V AC
[Ui] rated insulation voltage	500 V AC conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on

Mounting support	35 mm symmetrical DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	73 mm
Net weight	0.36 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals25 mm ² flexible Tunnel type terminals35 mm ² rigid
Tightening torque	3.5 N.m
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60947-2 IEC 60898
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Package 1 Weight	0.364 kg
Package 1 Height	0.730 dm
Package 1 width	0.530 dm
Package 1 Length	0.850 dm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)

24355 is replaced by the following product range:



Miniature Circuit Breaker: Acti9 iC60

Miniature Circuit Breakers up to 63A.

Products: 806