


Product description	M12-A male cable connector, Contacts: 5, unshielded, moulded cable, IP68, UL, PVC grey, 5 x 0.34 mm <sup>2</sup> , 2 m
Area	M12-A series 763
Part no.	77 3429 0000 20005-0200


## Illustration



## Scale drawing



## Contact arrangement (Plug-in side)



## Technical data

### General features

Part no.	<b>77 3429 0000 20005-0200</b>
	Alternative part no.: 79 3439 12 05
Notice	Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.
Connector design	male cable connector
Cable length	2 m
Version	male straight
Connector locking system	screw
Termination	moulded cable
Degree of protection	IP68
Cross-sectional area	0.34 mm <sup>2</sup> / AWG 22
Temperature range from/to	-25 °C / 90 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	97.00
Customs tariff number	85444290

### Electrical parameters

Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current (40 °C)	4,0 A
Insulation resistance	≥ 10 <sup>10</sup> Ω
Pollution degree	3
Overvoltage category	II

# Product data sheet

## Automation technology - sensors and actuators



Product description	M12-A male cable connector, Contacts: 5, unshielded, moulded cable, IP68, UL, PVC grey, 5 x 0.34 mm <sup>2</sup> , 2 m
Area	M12-A series 763
Part no.	77 3429 0000 20005-0200

Insulating material group	II
EMC compliance	unshielded

### Material

Housing material	PUR
Contact body material	PUR
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	Zinc die-cast nickel-plated
REACH SVHC	None (No pollutants)
SCIP number	SCIP-number not available

### Authorization/approvals

Approvals	UL
-----------	----

### Classifications

eCl@ss 11.1	27-06-03-11
ETIM 7.0	EC001855

### Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60529:1991;EN 60204-1:2018)
RoHS Directive	2011/65/EU (EN 50581:2012)

### Cable data - Structure of the cable

Cable diameter	5.2 mm
Cross section	5 x 0.34 mm <sup>2</sup>
Sheath material	PVC
Single-lead insulation	PVC
Single-lead structure	42 x 0.10 mm
Cable color	grey

### Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø
Bending cycles	>2 million
Permitted acceleration	5 m/s <sup>2</sup> + 1 m/s <sup>2</sup>
Travel distance, horizontal	5 m/s <sup>2</sup> -> 5 m
Travel distance, vertical	5 m/s <sup>2</sup> -> 2 m

Product description	M12-A male cable connector, Contacts: 5, unshielded, moulded cable, IP68, UL, PVC grey, 5 x 0.34 mm <sup>2</sup> , 2 m
Area	M12-A series 763
Part no.	77 3429 0000 20005-0200

Travel speed	≤ 200 m/min (5 m horizontal distance)
--------------	---------------------------------------

#### Cable data - Thermal properties

Temperature range cable in move from/to	-5 °C / 105 °C
Temperature range cable fixed from/to	-40 °C / 105 °C

#### Cable data - Other features

Halogen free	No
--------------	----

Product description	<b>M12-A male cable connector, Contacts: 5, unshielded, moulded cable, IP68, UL, PVC grey, 5 x 0.34 mm<sup>2</sup>, 2 m</b>
Area	<b>M12-A series 763</b>
Part no.	<b>77 3429 0000 20005-0200</b>

## Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP 67 and IP 68 are not suitable for use under water. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).